



Model 1130 - 2kW AC/DC Open-Framed Genset

(NSN 6115-01-548-2130)

Designed to Operate in Extreme Conditions

General Specifications

Engine: Hatz Diesel, 1B20, air-cooled, 24V electric-start

Alternator: GBI permanent-magnet alternator

Power output: (4,000 ft./95°F)

2kW Total of AC and/or DC

AC: 120VAC 60Hz-20amp GFCI receptacle

Wave form distortion: < 5%

Frequency variation: < 1%

DC: 28VDC-80amp current limited regulator-NATO connector

Voltage variation (ripple): < 5%

Operating Temperature range: -25°F (-31°C) ~ 125°F (51.7°C)

Fuels: Diesel DF-1, DF-2 and JP-8

Fuel consumption: .33gph (1.25lph)@ rated load

Fuel capacity/run time: 2gallons (7.57liters)/6 hours @ rated load

Sound: <78dBA @ 23' (7meters)

Dimensions: 27"X18.5"X22" (68.5X46.9X56.9cm)

Weight-dry: 166lbs (75kg)

Features

Electric and/or hand-start capable, on-board batteries, momentary AC overload capability for motor starting, digital DC amps/volts meters, AC output indicator and output circuit breaker, digital hourmeter

Applications

Artillery, Unmanned-Surveillance stations, Mobile combat and communications support

Goodman Ball, Inc. | 1-877-GBI-4PWR | www.goodmanball.com

